

## Economical Wall Heater



### Applications

- Breezeways
- Entryways
- Restrooms
- Small Offices
- Storage Rooms

The WLI wall heater is designed for recessed mounting into shallow 2-inch by 3-inch stud walls. It provides heat in a quiet, efficient manner. Single units can heat small areas and multiple heaters can be used in large or odd-shaped rooms.

- **Mounting Options:** Units can be surface or recessed mounted, vertically or horizontally, in one of four positions. A tapered recess box assures a tight fit when mounted into the wall.

## Standard Construction Features

**Heating Elements** – Steel finned tubular elements.

**Outlet Grille** – The louvered front grille is made from 20-gauge steel with rounded corners. The grille is finished with an epoxy-polyester powder paint in white or almond.

**Built-in Controls** – Automatic reset thermal cutout.

**Fan Motor** – Quiet, permanently lubricated axial fan operates at 38 dBA at 40 CFM for models up to 1,000 W and 41.3 dBA at 80 CFM for all models rated above 1,000 W.

**Installation Requirements** - The air outlet should be installed a minimum of ten inches above vinyl floors.

## Factory Built-in Options

Code	Description
D3	Disconnect Switch, 277V, Double-pole, 20 Amp
T1	Tamperproof Thermostat, Single-pole, 17 Amp
T2	Tamperproof Thermostat, Double-pole, 17 Amp
T5	Adjustable Thermostat, Single-pole, 17 Amp
T6	Adjustable Thermostat, Double-pole, 17 Amp

Double-pole thermostats include positive off feature.

## Field-Installed Options

(shipped loose for field installation into heater)


Catalog Number	Description
934-124647	Surface Mounting Box
934-124648	Adjustable Thermostat Kit, Single-pole, 17 Amp
934-124649	Tamperproof Thermostat Kit, Single-pole, 17 Amp
934-124650	Adjustable Thermostat Kit, Double-pole, 17 Amp
934-124651	Tamperproof Thermostat Kit, Double-pole, 17 Amp

**Standard colors** - Add W for white finish or A for almond finish to the end of catalog number.

**Special or custom colors** - See inside back cover for color codes to be added to end of catalog number.

**Remote Room Thermostat** – See page 96

# Economical Wall Heater



## Economical Wall Heater Listing

Watts	Volts	Total Amps (1)	CFM	Approximate Air Temperature Rise °F (°C)	Weight lb (kg)	Catalog Number
500	120	4.6	40	40 (22)	9 (4)	934U00500B
500/375	240/208	2.3/2.0	40	40/30 (22/17)	9 (4)	934U00500V
750	120	6.7	40	60 (33)	9 (4)	934U00750B
750/563	240/208	3.3/2.9	40	60/45 (33/25)	9 (4)	934U00750V
1000	120	8.7	40	80 (44)	9 (4)	934U01000B
1000/750	240/208	4.5/3.8	40	80/60 (44/33)	9 (4)	934U01000V
1250	120	10.8	80	50 (28)	9 (4)	934U01250B
1250/938	240/208	5.4/4.7	80	50/37 (28/21)	9 (4)	934U01250V
1500	120	12.9	80	60 (33)	9 (4)	934U01500B
1500/1125	240/208	6.5/5.6	80	60/45 (33/25)	9 (4)	934U01500V
2000/1500	240/208	8.5/7.4	80	80/60 (44/33)	9 (4)	934U02000V

(1) Total Amps = Heating element amps and motor amps.

All models listed are single-phase.

Standard colors - Add **W** for white finish or **A** for almond finish to the end of catalog number.

Special or custom colors - See inside back cover for color codes to be added to end of catalog number.