

COMPARISON CHART

Unit Heaters



Features	Washdown TRIAD®	IUH	UHIR	UCI	ULI	Vertical UVI	Portable UPI
Typical Applications	Food processing plants Marine duty Wastewater treatment plants	Factories Warehouses	Factories Mechanical rooms Workshops	Mechanical rooms Warehouses Workshops	Mechanical rooms Storage rooms	Gyms High bay areas Warehouses	Job Sites Workshops
KW Range	2 to 47	3 to 38.4	3.3 to 50	2 to 60	3 to 5	5 to 30	4.8
Voltages	up to 600/3	Up to 480/3	Up to 480/3	Up to 480/3	240/208/1	Up to 480/3	240/1
Airflow CFM	Up to 2400	Up to 1774	Up to 3100	Up to 2000	300	Up to 2300	300
Discharge	Horizontal	Horizontal	Horizontal or Vertical	Horizontal or Vertical	Horizontal	Vertical	Horizontal
Element Type	Stainless steel finned tubular	Stainless steel finned tubular	Stainless steel finned tubular	Stainless steel tubular or steel finned tubular	Stainless steel tubular	Steel finned tubular	Stainless steel tubular
Standard Construction	16 gauge stainless steel shroud and non-metallic NEMA 4X control enclosure	16 gauge galvanized steel shroud and control enclosure	20-14 gauge (depending on size) galvanized steel cabinet	8 & 20 gauge steel cabinet	20 gauge galvanized steel cabinet	18 gauge galvanized steel cabinet	22 gauge galvanized steel cabinet
Finish	Stainless steel	Beige polyester powder paint	Camel polyester powder paint	Almond polyester powder paint	Almond polyester powder paint	Almond polyester powder paint	Almond polyester powder paint
Mounting	Ceiling or wall	Ceiling or wall	Ceiling or wall	Ceiling or wall	Ceiling or wall	Ceiling	Portable
Agency Approvals	cUL _{us} & ABS	cUL _{us}	cUL _{us}	CSA _{us}	CSA _{us}	CSA _{us}	CSA _{us}