

Heat Trace Thermostats and Controllers



PART NUMBER:
HTTS-A
HTTS-L

DESCRIPTION: Mechanical thermostat
22 amp switching current SPDT, 120/250/480 V
Non-hazardous area
HTTS-A: ambient sensing
HTTS-L: line sensing



PART NUMBER:
HTTS-EPA
HTTS-EPL

DESCRIPTION: Mechanical thermostat
22 amp switching current SPDT, 120/250/480 V
Class I, Division 1 and 2, Group B,C,D
HTTS-EPA: ambient sensing
HTTS-EPL: line sensing



PART NUMBER:
1023953

DESCRIPTION: Single Stage Heavy duty Thermostat
Liquid filled sensing element with snap-acting contacts
Range: -30° to 100° F
Differential: 3 to 12° F between stages
Bulb Dimensions: 3/8" x 4"
Capillary Length: 8"
Resistive Rating: 22 amps, 120 to 277 volts




PART NUMBER:
HTCTRLR-1
HTCTRLR-2

DESCRIPTION: Heat trace microprocessor temperature controller
30 amp switching current SSR, 85-280 V
Class I, Division 2, Group B,C,D
Ground fault current alarm and trip
Alarm and communication capabilities
Single (-1) and dual circuit (-2)



PART NUMBER:
HTCTRLUNIT-5
HTCTRLUNIT-10
HTCTRLUNIT-X

DESCRIPTION: Master Trace multi-circuit temperature control panel 30 amp switching current SSR, 280 V max
Class I, Division 2, Group A,B,C,D
Ground fault current alarm and trip
Alarm and communication capabilities
5 circuit (-5), 10 circuit (-10), custom circuit quantity (-X)



PART NUMBER:
HTRTD-25

DESCRIPTION: Armored RTD cable and cord grip with 25' leads