

Indeeco's UHHP plenum heaters are versatile by design and are easily serviceable, if ever needed

Product Features

Standard Features

- 20 Gauge galvanized cabinet
- Variable speed motor
- Acoustically insulated with 1" fiberglass
- Access panels on both sides of cabinet
- 24 Volt controls / Disconnect switch
- Single point connection / Terminal blocks
- Dust tight control enclosure
- Air flow switch
- Automatic primary limit control and secondary fuse link
- Filter rack on inlet with throw away filter
- Inlet and outlet screens and duct connection

Optional Features

- Wall thermostat, unit thermostat or SSR control which proportionally regulates heat output
- Left hand connection in place of standard right

Industry Applications

- Concealed areas of high rise buildings
- Sporting event concession stands
- Plenum areas above large lobbies and foyers
- Large entry ways

Certifications



Conforms to ANSI/UL 1995
Certified to CAN/CSA C 22.2 No.236-11



Our products do more in a wide range of applications. **Expect More.**

Standard Plenum Heater Models

CATALOG NUMBER	KW	CFM RANGE	VOLTS / PHASE (1)	TOTAL AMPS for MOTOR & HEATER	STAGE	MOTOR VOLTAGE	FULL LOAD AMPS for MOTOR ONLY	MOTOR H.P.	WT. (LBS)	AVAILABILITY CODE (2)					
P-962U1N03C-DU6L4	3	70-270	208/1	15.4	1	277	1	1/15	98	AS					
P-962U1N03J-DU6L4			240/1	13.5		277	1								
P-962U1N03N-DU6L4			277/1	11.83		277	1								
P-962U1N03D-DU6L4			208/3	9.32		277	1								
P-962U1N03K-DU6L4			240/3	8.21		277	1								
P-962U1N05C-DU6L4	5	200-650	208/1	25.13	1	277	1.1	1/6	118						
P-962U1N05J-DU6L4			240/1	21.93		277	1.1								
P-962U1N05N-DU6L4			277/1	19.15		277	1.1								
P-962U1N05D-DU6L4			208/3	14.97		277	1.1								
P-962U1N05K-DU6L4			240/3	13.12		277	1.1								
P-962U1T05U-DU6L4	10	500-1200	480/3	7.11	1	480	1.1	1/4	141						
P-962U1N10D-DU6L4			208/3	29.45		277	1.7								
P-962U1N10K-DU6L4			240/3	25.75		277	1.7								
P-962U1N10U-DU6L4			480/3	13.72		277	1.7								
P-962U2N10D-DU6L4			208/3	29.45		277	1.7								
P-962U2N10K-DU6L4			240/3	25.75		277	1.7								
P-962U2T10U-DU6L4			480/3	13.72		480	1.7								
P-962U1N15D-DU6L4			15	500-1200		208/3	43.33				1	277	1.7	1/2	163
P-962U1N15K-DU6L4						240/3	37.78					277	1.7		
P-962U1T15U-DU6L4						480/3	19.74					480	1.7		
P-962U2N15D-DU6L4	208/3	43.3			277	1.7									
P-962U2N15K-DU6L4	240/3	37.78			277	1.7									
P-962U2T15U-DU6L4	20	750-1600	480/3	19.74	2	480	1.7	3/4	201						
P-962U2N20D-DU6L4			208/3	58.01		277	2.5								
P-962U2N20K-DU6L4			240/3	50.61		277	2.5								
P-962U2T20U-DU6L4	23	1300-2000	480/3	26.55	2	480	2.5	2 MOTORS @ 1/2 H.P. EACH	278						
P-962U2N23D-DU6L4			208/3	68.14		277	4.3								
P-962U2N23K-DU6L4			240/3	59.63		277	4.3								
P-962U2T25U-DU6L4	30	1800-2800	480/3	34.37	2	480	4.3	2 MOTORS @ 3/4 H.P. EACH	319						
P-962U2N30K-DU6L4			240/3	78.47		277	6.3								
P-962U2T30U-DU6L4			480/3	42.38		480	6.3								
P-962U2T35U-DU6L4	40	2000-3600	480/3	48.39	2	480	6.3	319							
P-962U2T40U-DU6L4			480/3	56.71		480	8.6								
P-962U2T45U-DU6L4			480/3	62.72		480	8.6								
P-962U2T50U-DU6L4	50		480/3	68.74	2	480	8.6								

(1) 60 Hz only

(2) AS = Assemble Stock, AS listed heaters ordered with custom (C) features are subject to longer lead times

Product Dimensions

P962 Series	A	B	L	Discharge	
				W	H
3 kW	12"	14"	32"	14"	8"
5 kW	14"	18"	36"	18"	8"
10 kW & 15 kW	18"	18"	36"	18"	10"
20 kW	18"	22"	36"	22"	10"
23 kW & 25 kW	18"	26"	36"	26"	10"
30 kW, & 35 kW	18"	44"	36"	44"	10"
40 kW, 45 kW, & 50 kW	18"	52"	36"	52"	10"

Note: Control panel access right hand (U6L4) is standard as shown. For panel on opposite side access specify left hand (U4L6). Control box depth depends on actual components. Consult factory for exact dimensions.

